

AMENDMENTS TO THE CLAIMS

1. (Canceled)

2. (Currently Amended) A printing module provided with a frame, an impression roller, a plate cylinder assembly comprising a plate cylinder which is provided with a print image and which, in use, with interposition of a substrate to be printed, abuts against the impression roller, and an anilox roller ~~and a doctor roller, the doctor roller taking up ink from an ink reservoir, the anilox roller being arranged between the doctor roller and adjacent to the plate cylinder, such that a desired amount of ink is taken off the doctor roller~~ transferred by the anilox roller ~~and transferred to the plate cylinder, the plate cylinder assembly being provided with a stationary shaft on which the plate cylinder is rotatably bearing-mounted, while on opposite sides of the plate cylinder a support is fixedly connected with the stationary shaft, the printing module comprising two receiving units disposed on opposite sides of the plate cylinder, which are connected with the frame, in which receiving units rest the supports when the plate cylinder assembly in the operative position is mounted in the printing module, while fixation means are provided for fixating the plate cylinder assembly in the receiving units, wherein the fixation means are situated substantially under the plate cylinder assembly,~~

wherein the fixation means comprise two rods which, at an upwardly directed end, are provided with a hook, the two hooks, on opposite sides of the plate cylinder, engaging the stationary shaft of the plate cylinder assembly when the plate cylinder assembly is in the operative position, while and means for exerting a pull force on the two rods ~~a pull force is exerted~~ for pressing the plate cylinder assembly into the receiving units.

3. (Original) A printing module according to claim 2, wherein the two rods are each connected, at the ends remote from the hooks, with a piston-cylinder assembly for adjusting the position of the rods in a longitudinal direction thereof and for exerting said pull force.

4. (Original) A printing module according to any one of claims 2-3, wherein the fixation means are further provided with bearing surfaces on which rests the plate cylinder assembly when the fixation means are in a release position, while the plate cylinder assembly in this release position is lifted out of the receiving units and is moved upwards, such that the plate cylinder assembly can be simply taken out of the printing module.

5. (Previously Presented) A printing module according to claim 2, wherein each rod is provided with a bearing surface, which bearing surface upon upward movement of the rods in the direction of the longitudinal axes of the rods automatically enters into engagement with the stationary shaft and thereby lifts the plate cylinder assembly from the receiving units.

6. (Previously Presented) A printing module according to claim 2, wherein the supports that are fixedly connected with the stationary shaft on opposite sides of the plate cylinder are supporting rings each having a diameter that matches the diameter of the plate cylinder, the receiving units each being provided with a supporting surface which is provided with a particular curve, the curve being such that the distance between plate cylinder and the anilox roller on the one hand and the distance between the plate cylinder and the impression roller on the other in

each case remain, in pairs, mutually equal at different diameters of plate cylinders, which are provided with rings of diameters matching the plate cylinders.

7. (Previously Presented) A printing module according to claim 1, wherein substantially above the receiving units, receiving means are provided for mounting additional processing means.

8. (Original) A printing module according to claim 7, wherein the receiving means comprise two guides.

9. (Previously Presented) A printing module according to claim 7 wherein the additional processing means comprise, for instance, substrate web inverting units, winders, unwinders, digital printheads, punching units, laminating or delaminating units or the like.

10. (Currently amended) A printing machine provided with at least one printing module provided with a frame, an impression roller, a plate cylinder assembly comprising a plate cylinder which is provided with a print image and which, in use, with interposition of a substrate to be printed, abuts against the impression roller, and an anilox roller ~~and a doctor roller, the doctor roller taking up ink from an ink reservoir, the anilox roller being arranged between the doctor roller and~~ adjacent to the plate cylinder, such that a desired amount of ink is ~~taken off the doctor roller~~ transferred by the anilox roller ~~and transferred to~~ the plate cylinder, the plate cylinder assembly being provided with a stationary shaft on which the plate cylinder is rotatably

bearing- mounted, while on opposite sides of the plate cylinder a support is fixedly connected with the stationary shaft, the printing module comprising two receiving units disposed on opposite sides of the plate cylinder, which are connected with the frame, in which receiving units rest the supports when the plate cylinder assembly in the operative position is mounted in the printing module, while fixation means are provided for fixating the plate cylinder assembly in the receiving units, wherein the fixation means are situated substantially under the plate cylinder assembly, wherein the fixation means comprise two rods which, at an upwardly directed end, are provided with a hook, the two hooks, on opposite sides of the plate cylinder, engaging the stationary shaft of the plate cylinder assembly when the plate cylinder assembly is in the operative position, and,

means for exerting while on the two rods a pull force ~~is exerted~~ for pressing the plate cylinder assembly into the receiving units when the plate cylinder is in the operative position.

11. (New) A printing module provided with a frame, an impression roller, a plate cylinder assembly comprising a plate cylinder which is provided with a print image and which, in use, with interposition of a substrate to be printed, abuts against the impression roller, and an anilox roller, the anilox roller being arranged adjacent to the plate cylinder, such that a desired amount of ink is transferred from the anilox roller to the plate cylinder, the plate cylinder assembly being provided with a stationary shaft on which the plate cylinder is rotatably bearing- mounted, while on opposite sides of the plate cylinder a support is fixedly connected with the stationary shaft, the printing module comprising two receiving units disposed on opposite sides of the plate cylinder, which are connected with the frame, and are configured to provide a rest for the

supports when the plate cylinder assembly in the operative position is mounted in the printing module; and fixation means comprising two rods located on opposite sides of the plate cylinder, each of which is provided at an upwardly directed open end with a hook for engaging the stationary shaft of the plate cylinder assembly when the plate cylinder assembly is in the operative position, and means for exerting a pull force on the rods for pressing the plate cylinder into the receiving units, and wherein the fixation means are situated substantially under the plate cylinder assembly and not above the top of the plate cylinder to permit free access to the plate cylinder assembly from above the plate cylinder assembly.

12. (New) A printing module according to claim 1, wherein the receiving units are each provided with a supporting surface which is provided with a particular curve, the curve being such that the distance between plate cylinder and the anilox roller on the one hand and the distance between the plate cylinder and the impression roller on the other in each case remain, in pairs, mutually equal for different diameter plate cylinders provided with rings of diameters matching the plate cylinders.